

# KEUV-CV

Protection of cooling towers, water distribution piping and heat exchangers

## Solution of problems with clogging and incrustation

- Brings water into calcium carbonate balance
- Continuously removes all impurities from cooling water
- Disinfects water and prevents the formation of biofilms
- Minimal power consumption
- ❷ Fully automated and unattended oparation
- **②** Environmentally friendly, no use of chemicals







#### WHAT DOES KEUV-CV SERVE FOR

KEUV-CV treatment plant for cooling water is designed for the protection of cooling towers and heat exchangers from clogging, for continuous filtration of insoluble substances and for disinfection of water in cooling circuits. This way it replaces several devices at a time.

While cooling water gets heated calcium carbonate balance shifts in the direction of salts separation - particularly calcium carbonate. Moreover, impurities contained in the air get absorbed in the cooling towers.

These impurities together with separated salts cause the formation of sediments, biofilms and rusts in the cooling circuit. Water treatment is therefore an indispensable part of the process.

In case of large circuits, both opened and closed ones, this problem can be solved with dosing of various chemicals like corrosion inhibitors, dispersants, biocides and bio-dispersants. This traditional system of chemical protection is not environmentally friendly, requires qualified and skilled operation staff, and controls carried out in a chemical laboratory.

These drawbacks can be eliminated by using the electrolytic water treatment plant for cooling water, KEUV-CV.

#### HOW DOES KEUV-CV FUNCTION

KEUV-CV water treatment plant is a compact apparatus that contains an electrolyser which is integrated inside a pressure filter. When exposed to direct current, controlled formation of limescale occurs on the cathode and oxidation processes on the anode. Oxidised forms create a precipitate that gets filtered out on a sand filterbed. Several other impurities from water get caught on the iron precipitate as well. The sand bed gets automatically flushed out in regular intervals and the impurities wash away into the sewerage system. The water treatment plant usually gets installed on a bypass piping at the output of cooling circuit pumps. It usually is 5 to 10 per cent of the circulating cooling water that passes through the water treatment plant. The effect of KEUV-CV shows immediately. The process is environmentally friendly, without using chemicals and it requires no involvement of the operation staff.

### INSTALLATION OF THE EQUIPMENT

We have to transport the water treatment plant KEUV-CV to the place designated for installation, we connect it to the cooling circuit and to the electricity network. The outlet of the flushing water has to be introduced into the sewerage system, and then we set up the equipment and put it into operation.



Environmentally friendly



**€** Economical



Without chemicals



No compromises



	KEUV-CV 01	KEUV-CV 02	KEUV-CV 03
For circuits with flow rate up to (m³/h)	100	200	400
DN input/output (mm)	50	50	80
Maximum power consumption (W)	120	180	250
Maximum operation temperature (°C)	60	60	60
Maximum operation overpressure (MPa)	1	1	1